



SNA GmbH

Hochleistungs - Schmierstoffe



Gutenbergstraße 2d,
59174 Kamen,
Germany
Tel. +49 (0) 151
64695831
Internet:
<http://snalube.com> e-
mail:
info@snalube.com

Description

Application

Specification

Typical Characteristics

Product Information

Quelle QX – SuperTech 0W16 SP

Quelle QX 0W16 is a very high performance, ultra-low viscosity fluid, fully synthetic lubricant for gasoline and hybrid engines, including the ones complying with ILSAC GF-6B standard. It is formulated to help increase engine efficiency and improve fuel economy benefits, while providing outstanding overall engine protection.

This product meets or exceeds the requirements of the latest API and ILSAC industry specifications for petrol and hybrid engine oils, as well as the requirements of many major American engine manufacturers. Suitable for use in passenger cars.

Performance level:

ILSAC GF-6B
API SP

0W16 SP		
Property	Unit	Typical Values
Density at 15 °C	kg/l	0.838
Viscosity -15 °C	mPa.s	6200
Viscosity 40 °C	mm ² /s	35.95
Viscosity 100 °C	mm ² /s	7.2
Viscosity Index		154
Flash Point COC	°C	230
Pour Point	°C	-50
Total Base Number	mgKOH/g	8
Sulphate Ash	%	0.78

The data mentioned in this product information sheet are meant to enable the reader to orient himself about the properties and possible applications of our products. Although this overview is composed with all possible carefulness on the stated date, the composer does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product-choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification. You can download a recent material safety data sheet of this product on our website.