



SNA GmbH
Hochleistungs - Schmierstoffe



Gutenbergstraße 2d,
59174 Kamen,
Germany
Tel. +49 (0) 151
64695831
Internet:
<http://snalube.com> e-
mail:
info@snalube.com

Description

Application

Specification

Typical Characteristics

Product Information

Quelle QX- Moto 4T 20W50 SN

Quelle QX – Moto 4T 20W50 SN is fully synthetic 4-stroke engine oil for modern high performance sports bikes that increases engine acceleration and power right up to maximum rpm.

Its design ensures maximum engine performance without sacrificing engine durability thus giving a significant benefit over other types of engine oils.

It provides optimum protection of the engine, clutch and gears

Advantages

Extreme high temperature air-cooled and water-cooled engine performance

Excellent oil consumption and volatility control at high speeds

Excellent shear stability to prevent viscosity break down

Complies with requirements of catalyst equipped engines

APPLICATION

Quelle QX – Moto 4T 20W50 SN is designed for high performance sports bikes to deliver optimum power and protection in all conditions where API SN (and below) and JASO MA2 are recommended.

Performance level:

API SN

JASO MA2

4T 20W50 SN		
Property	Unit	4T
Density @15 °C	Kg/l	0.88
Viscosity 100 °C	mm ² /s	18
Viscosity 40 °C	mm ² /s	156
Viscosity Index		127
Pour Point	°C	-33
Flash Point	°C	206

The data mentioned in this product information sheet are meant to enable the reader to orient himself about the properties and possible applications of our products. Although this overview is composed with all possible carefulness on the stated date, the composer does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product-choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.
You can download a recent material safety data sheet of this product on our website.